



ISO Mounting Pad Dimensions

Dimensions: inches (millimeters)

| Flanged type | d_1 | d_2 | d_3 | d_4 | h_1 max. | h_2 min. | Number of screws, studs or bolts |
|--------------|-------------|-------------|-------------|-------|------------|------------|----------------------------------|
| F03 | 1.81 (46) | .984 (25) | 1.42 (36) | M5 | .118 (3) | .315 (8) | 4 |
| F04 | 2.12 (54) | 1.18 (30) | 1.65 (42) | M5 | .118 (3) | .315 (8) | 4 |
| F05 | 2.56 (65) | 1.37 (35) | 2 (50) | M6 | .118 (3) | .354 (9) | 4 |
| F07 | 3.54 (90) | 2.16 (55) | 2.75 (70) | M8 | .118 (3) | .472 (12) | 4 |
| F10 | 4.92 (125) | 2.75 (70) | 4.00 (102) | M10 | .118 (3) | .590 (15) | 4 |
| F12 | 5.90 (150) | 3.34 (85) | 4.92 (125) | M12 | .118 (3) | .708 (18) | 4 |
| F14 | 6.88 (175) | 3.94 (100) | 5.50 (140) | M16 | .157 (4) | .945 (24) | 4 |
| F16 | 8.26 (210) | 5.12 (130) | 6.50 (165) | M20 | .197 (5) | 1.18 (30) | 4 |
| F25 | 11.81 (300) | 7.87 (200) | 10 (254) | M16 | .197 (5) | .945 (24) | 8 |
| F30 | 13.78 (350) | 9 (230) | 11.75 (298) | M20 | .197 (5) | 1.18 (30) | 8 |
| F35 | 16.34 (415) | 10.25 (260) | 14 (356) | M30 | .197 (5) | 1.77 (45) | 8 |
| F40 | 18.70 (475) | 11.81 (300) | 16 (406) | M36 | .315 (8) | 2.12 (54) | 8 |
| F48 | 22 (560) | 14.57 (370) | 19 (483) | M36 | .315 (8) | 2.12 (54) | 12 |
| F60 | 27 (686) | 18.50 (470) | 23.75 (603) | M36 | .315 (8) | 2.12 (54) | 20 |